California Energy Commission Distributed Generation OII Order No 99-1103-11

Distributed Generation Issues

12/6/99

Vic Romero
San Diego Gas & Electric

Safety is Job 1

¥Safety is the paramountissue

¥Worker Safety

¥Public Safety

¥Utility high voltage safety philosophy based on multi-layer safety approach

¥Safety can be managedby proper interconnection standards

Safety Issues

¥Possibility of Backfeed/Islanding


¥Equipment fault duty exceeding limits

¥Overloaded equipment and conductors

¥Fuse/relay coordination

¥Reliability and power quality are closely related to safety

Transmission & Distribution System <u>Distribution System</u>




¥ Radial system

¥ Unidirectional power flow

¥ Fault current from bus only

¥ Typical load: 300-600 amps (12 Mw max)

Distribution System with DG



¥ Additional fault current available

¥ Fault current from new direction

¥ Must clear fault at multiple locations

Protection Priorities - Utility

- ¥ Producer clears all faults on Producer equipment
- ¥ Producer isolates for all faults on utility system
- ¥ Producer will not supply islanded utility load
- ¥ Producer will not energize dead bus
- ¥ Producer will not close out-of-sync

Priorities - Producer

- ¥ Minimize costs
- ¥ Expedite approval process- construction and interconnection
- ¥ Streamlined interconnection guidelines
- ¥ Provide protection for all plant equipment
- ¥ Minimize Producer operational issues

Mutual Goals for Interconnection Guidelines

- ¥ Provide for safe, efficient operation
- ¥ Simplify interconnection process
- ¥ Recognize relevant technologies
- ¥ Encourage certification of systems

Rule 21 - Interconnection Guidelines

- ¥ Interconnection evaluation
- ¥ Design & Operating requirements
- ¥ Protection requirements
- ¥ Addresses transformer and manual disconnects requirements

In Summary

- ¥ Safety must continue to be paramount issue
- ¥ Interconnection evaluation could be streamlined for smaller sizes
- ¥ Concept of pre-certification is viable
- ¥ Safety issues can be managed by mutual cooperation and proper interconnection standards